



COPPER FOIL SLITTING MACHINE



COPPER FOIL SLITTING MACHINE



Model No.	SLS-ET150HI
Applicable Material	Copper foil 6-35 μ
Tension Range	10-30 Kg for unwinder and 15-60 Kg for rewinder
Parent-web Width	1060-1480 mm
Parent-web Diameter	ϕ 550 mm
Slitting Width	200-1260 mm
Maximum Finish-roll Diameter	ϕ 500 mm
Unwinding Core Inner Diameter	As required
Rewinding Core Inner Diameter	ϕ 3" & ϕ 6"
Machine Speed	5-150 M / min.
Machine Color	White
Power Supply	As required

- The unwinder and rewinder are opposite.
- The working speed depends on the material condition and slitting width.

Full range of specifications and sizes were developed for high-tech industries. Our copper foil slitting machine are widely used in various types of fiberglass epoxy resin copper clad laminate, multilayer printed circuit board, flexible circuit board, IC-substrate, lithium-ion battery, and paper-phenolic resin copper clad laminate.


LITHIUM-ION BATTERY INDUSTRY

- Consumer Electronics
- Cell Phone
- Power Batteries
- Energy Storage Batteries
- Electric Vehicles

FEATURES



Roller surface special treatment



Adjustable unwind stand



Gap adjustable nip roller



Shear Cutter



Coreless trimmed waste rewind stand



Rewind contact roller



Rewind roll weighing system



Siemens PLC control & drive system

DAH BAH, Discover the Best.



No. 69-10, Sec. 2, Chung Shin Rd.,
Tali Dist., Taichung City 412, Taiwan
Tel. +886-4-2483-2477 **Fax.** +886-4-2483-0852
E-Mail. dahbah@dahbah.com.tw
www.dahbah.com.tw

