

LDPE / LLDPE Plastic Inflation Machine

STRETCH FILM

PE保鮮膜吹袋機

KML

KML-45S / 55S



KANG CHYAU

Specification



Whole Plant for Plastic Bags Making Machine

MODEL 機型	KML-45S	KML-55S
SUITABLE MATERIAL 適用原料	LDPE / LLDPE	LDPE / LLDPE
FILM THICKNESS 膜厚	0.008~0.10 mm	0.008~0.10 mm
FILM WIDTH RANGE 膜寬	600 mm	900 mm
FILM OUTPUT 最大膠膜產量	20~55 kgs / hr	30~72 kgs / hr
EXTRUDER UNIT 主機部份		
SCREW DIAMETER / TYPE 螺桿直徑 / 型號	45	55
SCREW L / D RATIO 螺桿長徑比	30 : 1	30 : 1
HEATING CAPACITY 電熱量	9.8 kw	14 kw
AUTO THERMO CONTROL 溫控點	4 zone	4 zone
BARREL COOLING FAN 螺桿冷卻風扇	1/8 hp × 2	1/8 hp × 3
DRIVING MOTOR 主驅動馬達	AC 20 hp + INVERTER	AC 30 hp + INVERTER
DIE UNIT 模頭部份		
DIE DIAMETER 模頭直徑	Ø 175 mm	Ø 250 mm
AIR RING DIAMETER 風環直徑	Ø 225 mm	Ø 300 mm
HEATING CAPACITY 電熱量	6.5 kw	9 kw
AUTO THERMO CONTROL 溫控點	2 zone	3 zone
COOLING BLOWER 冷卻風車	3 hp + INVERTER	5 hp + INVERTE
TAKE-UP UNIT 引取部份		
TAKE-UP ROLLER 引取輪寬	760 mm	1100 mm
EFFECTIVE WIDTH 有效引取輪寬	660 mm	900 mm
TAKE-UP MOTOR 引取馬達	AC 1/2 hp	AC 1/2 hp
TAKE-UP SPEED 引取速度	75 m / min	65 m / min
BUBBLE GUIDE	ROLLER TYPE	
WINDING UNIT 捲取部份		
ROLLER WIDTH 捲取輪寬	760 mm	1100 mm
WINDING WIDTH 有效捲取寬度	660 mm	900 mm
WINDING MOTOR 捲取馬達	DC 1/2 hp × 3	DC 1/2 hp × 3
EQUIPMENT 配備	AUTO TENSION CONTROLLER WASTE COLLECTING WINDER ADHESIVES AUTO - FEEDER	AUTO TENSION CONTROLLER WASTE COLLECTING WINDER ADHESIVES AUTO - FEEDER

REMARK : The above machine specification and production range can be changed without any notice due to kind of different application.

型錄上之圖片及係數只備參考其尺寸、規格、樣式會因客人所訂購的配件不同而有所改變

康喬工業有限公司

KANG CHYAU INDUSTRY CO., LTD.

247 新北市蘆洲區復興路 227 巷 28 弄 2-10 號

No. 2-10, Aly. 28, Ln. 227, Fuxing Rd., Luzhou Dist., New Taipei City 247, Taiwan

Mail Box: P. O. Box 5-56, Luzhou Dist., New Taipei City 247, Taiwan

Tel: +886-2-22856880~1 Fax: +886-2-22856883

E-mail: kang.chyau@msa.hinet.net Internet: www.kangchyau.com.tw

