

TWIN Servo Motor Driven Side Sealing Plastic Bag Making Machine

雙伺服馬達驅動電腦按鍵式 邊封袋專用自動封切機



SHSS-T



興享機器興業有限公司
SING SIANG MACHINERY CO., LTD.

70969台灣台南市和順工業區永安路66號 TEL : +886-6-356-3297 FAX : +886-6-356-7267

66 Yung-An Road, Ho-Sun Industrial, Tainan, Taiwan

<http://www.bag-machine.tw>

Email: ssmtaiwan@gmail.com

Toll-Free Service Hot line: 0800-030-567

YouTube [ssm3563297](https://www.youtube.com/channel/UCssm3563297)





● 後入料裝置 Infeed Device



● 氣壓昇降式封刀 Air Cylinder Lifter Type Sealing Blade



● 雙印刷電眼 Double Mark Sensor

特點：

1. 雙伺服馬達驅動、機體傳動輕快、穩定，每分鐘可生產240個袋子。
2. 人性化電腦操作面板，易懂易操作。
3. 電腦按鍵式製袋長度自動調整，出袋長度精準，廢料少。
4. 機械結構設計精簡、組裝精密、牢固耐用、保養簡易。
5. 操作簡便，封切口整齊美觀又牢固、袋子表面不拖痕。
6. 電眼印刷追蹤、袋子印刷位置精準，當發現印刷失準機器自動停機。

Features :

1. Twin Servo Motor Driven, Efficient mechanical structure produce 240 bags per minute.
2. User-friendly Control Panel, easy to understand easy to operate.
3. Digital control for production length adjusting, precise and less wastage.
4. Simple design, assemble precisely, durable, and easy for maintaining.
5. Easy operating, Pleasant cutting and sealing, with high firmness and no scratch.
6. Real time printing tracing control for accurate registration, when printing error occurred machine will stop automatically.

選購配備 Optional Accessories :

1. 輸送帶裝置 Conveyer Stacker
2. 空壓打孔裝置 Punching Device
3. 書包裝裝置 Twin Bag Sealing Device
4. 平邊線裝置 Central Sealing Line Punch Device
5. 自動對邊供料架 Rear Unwinder with EPC Device
6. 點斷線裝置 Perforated Line Device

型號 Model	產能 Output Cycle/min.	封寬 Bag Width	封長 Bag Length	伺服馬達 Servo Motor	主馬達 Main Motor	變頻器 Inverter	電熱 Heater	總電量 Power Consumptipn	機器尺寸 Machine Dimension (LxWxH)	淨重 Machine Weight	包裝 Packing M3	毛重 Gross Weight
SHSS-T-30	20~120	300mm x 2	Max 750mm	二組 Two Set	2H4P	3HP	2.5KW	6KW	4100x1420x1710	1400kg	8.5m ³	1700kg
SHSS-T-36	20~100	350mm x 2	Max 750mm		2H4P	3HP	3.0KW	7.2KW	4100x1570x1710	1550kg	9.5m ³	1900kg
SHSS-T-42	20~80	400mm x 2	Max 750mm		2H4P	3HP	3.5KW	7.7KW	4100x1720x1710	1700kg	10.5m ³	2100kg
最小製袋寬度 Minimum production width					# Specification are subject to change without notice (變更設計恕不另行通知)							
標 準 型 / Standard Model				Min. 50m/m								
35mm 機型 / Medium-Size Model				Min. 35m/m								

Specification are subject to change without notice (變更設計恕不另行通知)