

Double Degasification Plastic Waste Reclaiming Pelletizing Machine

雙脫氣塑膠廢料再生製粒機

AP-85SP-H / 100SP-H / 120SP-H / 150SP-H

本機乃針對各種廢棄之PP、PU、PE、PS、ABS或尼龍等之製品，先經粉碎，再經本機處理再生製成原料使用。

The machine is specially for various PP, PU, PE, PS, ABS & NYLON waste process. After crushing and granulating, those re-processed & reclaimed waste material are as ready for new material use.



 **APEX-PLAS**
apex

Double Degasification Plastic Waste Reclaiming Pelletizing Machine

雙脫氣塑膠廢料再生製粒機

螺旋輸送機



SCREW CONVEYOR

水冷卻設備



WATER COOLING EQUIPMENT

油壓換網



HYDRAULIC LOAD / UNLOADING
NETTING MOLD

儲料桶



STORAGE BARREL

切粒機



PELLETIZER MACHINE

規格 SPECIFICATIONS

形式 Model	AP-85SP-H	AP-100SP-H	AP-120SP-H	AP-150SP-H
第一押出機 1st Extruder				
押出量 Extruding cap.	100-180 kgs / hr	200-280 kgs / hr	300-380 kgs / hr	350-500 kgs / hr
螺旋徑 Screw dia.	85 mm	100 mm	120 mm	150 mm
長徑比 Screw L / D ratio	36:1	36:1	36:1	36:1
驅動動力 Driving power	40 HP	60 HP	75 HP	100 HP
加熱區域 Heating zone	5	7	9	11
電熱容量 Heating cap.	36 kw	40 kw	60 kw	82 kw
速度控制方式 Speed control style	Two step	Two step	Two step	Two step
強制給料動力 Forced feed power	3 HP vs	3 HP vs	5 HP vs	5-1 / 2 HP vs
油壓換網動力 Hyd. net changing power	3 HP	3 HP	3 HP	5 HP
第二押出機 2nd Extruder				
螺旋徑 Screw dia.	90 mm	105 mm	125 mm	155 mm
長徑比 Screw L / D ratio	12:1	12:1	12:1	12:1
驅動動力 Driving power	10 HP vs	20 HP vs	25 HP vs	30 HP vs
電熱容量 Heating cap.	10 kw	14 kw	20 kw	24 kw
冷卻水槽 Cooling Water Tunnel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
切粒機 Pellet cutting m / c	—	—	—	—
驅動動力 Driving power	2 HP vs	3 HP vs	5 HP vs	7-1 / 2 HP vs
機械重量 M / C Weight	2600 kgs	3200 kgs	4500 kgs	6300 kgs
裝箱才數 Packing(約 approx.)	10 m	15 m	18 m	24 m



APEX-PLAS INDUSTRIAL CO., LTD.

11F-1, No.393, Fuxing Rd., Taoyuan City, Taoyuan County 33066, Taiwan
Tel : +886-3-3319116 Fax : +886-3-3319339

www.apexplas.com
mail : ap@apexplas.com