



## **KSF-2020-2L**

### **Multi-Layer Blow Molding Machine**

單層至多層共擠出中空成型機

蓄積容積 / *storage* 36L (客製化)

| Specification |                      |         | KSF-2020-2L                                       |
|---------------|----------------------|---------|---------------------------------------------------|
| 螺桿直徑          | Screw Diameter       | mm      | 90 mm + 100 mm                                    |
| 模板尺寸          | Platen Size          | —       | 2000 mm x 2000 mm                                 |
| 鎖模力           | Clamping Force       | —       | 160 ton                                           |
| 押出機馬達         | Extruder Motor       | HP      | 75 HP + 100 HP                                    |
| 押出機速率         | Extruder Speed       | kg / hr | 380 (MAX)                                         |
| 控制系統          | Control System       | —       | 電腦化色彩觸控操作<br>Computerised with Color Touch Screen |
| 厚薄控制          | Parision Control     | —       | 100 Points                                        |
| 模頭            | Die Head             | —       | 蓄料式 Storage Type                                  |
| 蓄料量           | Storage Quantity     | —       | 36 L                                              |
| 開隙            | Daylight             | —       | 700 mm ~ 2500 mm                                  |
| 押出機升降         | Platform Movement    | —       | 5 HP 減速機馬達 Electric Motor                         |
| 油壓幫浦馬達        | Hydraulic Pump Motor | —       | 20 HP + 20 HP (節能設計 Energy Saving)                |

★ 本目錄中所有規格若有變動，恕不另行通知

Figures and data in this catalogue are subject to change without prior notice due to constant research and development



油壓系統 Hydraulic System



人機控制系統  
Man-Machine Control System



直截式押出機  
Direct Type Extruders



夾模臂 Clamp Arm



昇降台 Lift Table