



TANDAM TYPE CO-EXTRUSION PP / PE LAMINATION MACHINE

FK/TLAFM-100/75/125/90-1500



Extrusion Excellence

www.fki.com

FK/TLAFM-100/75/125/90-1500

TANDAM TYPE CO-EXTRUSION PP / PE LAMINATION MACHINE




Design Line Speed

300 MPM



Max. Running Speed

250 MPM



Roller width

1500 mm



Lamination Thickness

0.01~0.04 mm



Extruder B / A / D / C : 100mm / 75mm / 125mm / 90mm, 100HP / 75HP / 200HP / 75HP, L/D 32:1

3 Layer Feedblock : ABA / BBA / ABB / CDC / CDD / DDC, CLOEREN

Main Unwinder : 1000mmΦ, Top & Bottom Cutter, 3" + 6" Air Shaft

1st, 2nd Primer Coating & Drying Unit : Arch Type , Drying Length 5.2m, Heating Capacity : 288 KW

1st, 2nd Lamination Unit : 600mmΦ / 800mmΦ Chill Roller, KOKA / FKI Brand

1st, 2nd Secondary Unwinder : 800mmΦ, Top & Bottom Cutter

Rewinder : 1000mmΦ, Top & Bottom Cutter, 3" + 6" Air Shaft

Drive & PLC: SIEMENS, Germany

AVG. Power Consumption: 195KW / 270A/hr, 240KW / 333A/hr

Max. Extrusion Capacity : 320 / 150 / 550 / 200 kg/hr

Manual T-Die, CLOEREN

Drive Motor : 20 HPx 2

Drive Motor : 15 HP / 20 HP

Drive Motor : 15 HP x 2, 3" + 6" Air Shaft

Drive Motor : 7.5HP Constant HP Motor x 2

17" HMI, SIEMENS, Germany

Machine Space : 34 x 15 x 6M (Lx Wx H)

We reserve the right to make technical changes without prior announcement. All rights reserved. ©2018 FONG KEE INTERNATIONAL MACHINERY CO., LTD.

Designed by Potarto 2018-07, +886-4-24517070



FONG KEE INTERNATIONAL MACHINERY CO., LTD.

No. 168, Cheng Pei First Rd., Yongkang Dist., Tainan City 71042, Taiwan

Tel. +886-6-2532157 Fax. +886-6-2533079 Email. sales@fki.com



www.fki.com uCloud