

INTERLEAVED DRAW TAPE BAG ON ROLL CONVERTING SYSTEM





INTERLEAVED DRAW TAPE BAG ON ROLL

TA-IPD-S1 Series



Flowchart



Features

- High speed integrated servo-driven system, suitable for poly draw, and conventional garbage bags on roll.
- Hot air sealing system for horizontal lip sealing features stable sealing.
- Draw tape feeding system for auto inserting the tape, double unwind device for auto exchange draw tape.
- Equipped with PLC touch screen operator friendly control system.
- Servo driven (4 axis) shuttle bag making machine for complete synchronization of in-feed / out-feed, seal and shuttle motion.
- Compact rotary overlap bag winder.
- 2 in 1 rewinder, available for perforation and interleaved draw type bag on roll.
- Optional label dispenser.

Specifications

* Specification subject to change without notice

MODEL	TA-1000IPD-S1	TA-1200IPD-S1
Bag Width (mm)	400 ~ 1000	400 ~ 1000
Bag Length (mm)	450 ~ 900	450 ~ 1200
Thickness (mm)	HDPE 0.008 ~ 0.025 LDPE 0.020 ~ 0.100	HDPE 0.008 ~ 0.025 LDPE 0.020 ~ 0.100
Draw-tape Width (mm)	100	100
Max. Dia. of Production (mm)	110	110
Max. Width of Production (mm)	100 ~ 275	100 ~ 275
Machine Speed (m/min)	20 ~ 130	20 ~ 130
Power Required (kw)	52	52.4

www.lungmeng.com.tw



uCloud



LUNG MENG MACHINERY CO., LTD.

Headquarters

No. 20, Huan Kung Rd.,
Yung Kang Ind. Area,
Tainan City 710, Taiwan
T +886-6-232-1126
F +886-6-232-1178
E sales@lm-hg.com

Taipei Office

7F., No.12-10, Sec. 2,
Zhongyang S. Rd.,
Beitou Dist.,
Taipei City 112, Taiwan
T +886-2-2937-6599
F +886-2-2937-9518