

Servo Motor Driven Perforating Bag Making Machine

伺服馬達驅動 點斷袋製袋機

SHPC



興享機器興業有限公司
SING SIANG MACHINERY CO., LTD.

70969台灣台南市和順工業區永安路66號 TEL : +886-6-356-3297 FAX : +886-6-356-7267

66 Yung-An Road, Ho-Sun Industrial, Tainan, Taiwan


<http://www.bag-machine.tw>

Email: ssmtaiwan@gmail.com

Toll-Free Service Hot line: 0800-030-567

Web Site: www.興享.tw





● 氣壓式收台 Pneumatic Type Rewinder



● 點斷裝置 Perforating Device



● 雙入料裝置 Twin Line Infeed Device

特色：

1. 張數計數控制。一旦張數到達設定值，蜂鳴器會響機器自動停止。
2. 入料電眼控制入料速度及確保機器的穩定性。
3. 可雙線生產。
4. 捲袋偏邊可調整成品整齊美觀。
5. 捲袋斷袋，自動停機。
6. 本機械可用於點斷袋，亦可選購做底封袋及成衣袋一般型封印機。

Features：

1. Equipped with product counter. Once the set bag quantity is reached, the machine stops automatically and sounds an alarm.
2. Uses sensors to control feeding speed and ensure stability.
3. Double line production.
4. Adjustable taking up speed for making products neat and beautiful.
5. Automatic stopping when it is rewinder line is break.
6. This machine can be used to perforate rolled bags, and can be replaced with bottom sealing bag and garment bag for optional.

製袋種類

BAGS AVAILABLE：


平口袋

Bottom Sealing Bag




垃圾袋

Garbage Bag



成衣袋

Garment Bag



規格 SPECIFICATION：

型號 Model	產能 Output Cycle/min.	捲袋寬 Rewind Width	捲袋長 Rewind Length	封厚 Film Thickness	主馬達 Main Motor	總電量 Power Consumption	機器尺寸 Machine Dimension (LxWxH)	淨重 Machine Weight	毛重 Gross Weight
SHPC-20	Max 120	400m/m or 200m/m ×2	Max 1000m/m	0.01~0.06 m/m	2HP4P	4.0KW	3630×1450×1650	1100kg	1300kg
SHPC-24	Max 120	500m/m or 250m/m ×2	Max 1000m/m	0.01~0.06 m/m	2HP4P	4.2KW	3630×1550×1650	1200kg	1450kg
SHPC-30	Max 120	600m/m or 300m/m ×2	Max 1200m/m	0.01~0.06 m/m	2HP4P	4.5KW	3630×1700×1650	1300kg	1600kg
SHPC-36	Max 90	800m/m or 400m/m ×2	Max 1200m/m	0.01~0.06 m/m	2HP4P	5.7KW	3630x1855x1650	1400kg	1750kg
SHPC-42	Max 90	1000m/m or 500m/m ×2	Max 1200m/m	0.01~0.06 m/m	2HP4P	6.2KW	3630x2010x1650	1500kg	1900kg

Specification are subject to change without notice (變更設計恕不另行通知)