KNEADER MACHINERY CO., LTD.

非加壓雙挽式混合機

DOUBLE ARM OPEN TYPE KNEADER





特性

這款非加壓雙挽式混合機可用多種的攪拌葉片 和各種倒料方法與混練方式。非加壓雙挽式混 合機也可以應用在相當廣泛的中黏度物質工 業,像是膠黏劑、凝結的磁性物質與化學物質 的混練。



BANBURY TYPE BLADE

FEATURES

The KD double-arm kneader is available with a variety of blades in different shapes as well as with number of discharging methods and mixing conditions. This KD double arm kneader has already achieved considerable renown in a wide range of industries that deal with such high and medium-viscosity materials as adhesives, agglutinates magnetic materials and chemical material mixing.



SIGMA TYPE BLADE



Z TYPE BLADE

應用

- 膠黏劑
 - ■印刷油墨
- 熱熔物質
- ■膠帶 対
- ■油封物質
- 陶瓷■ 熱固型樹脂■ 磁性複合物■ 化學藥品■ 矽膠
- Applications
- AdhesivesTapes

Ceramics

Chemicals

- S
- Printing inks
- Sealing materials
- Thermosetting resins
- Pigments

Hot-melt materials

- Magnetic compounds
- Silicon rubber

機 型 Model	總容量 Total capacity	工作容量 Working capacity	主馬力 Main motor
(D-50-10/15/20/30N	100 Liters	50 Liters	10/15/20/30 HP
CD-100-10/20/30/50N	200 Liters	100 Liters	10/20/30/50 HP
(D-200-20/30/50/75N	350 Liters	200 Liters	20/30/50/75 HP
(D-300-30/50/75/100N	500 Liters	300 Liters	30/50/75/100 HP
(D-400-30/50/75/100N	700 Liters	400 Liters	30/50/75/100 HP
(D-500-30/50/75/100N	850 Liters	500 Liters	30/50/75/100 HP
(D-600-75/100/150N	1000 Liters	600 Liters	75/100/150 HP
(D-1000-100/150N	1900 Liters	1000 Liters	100/150 HP

利拿機械工業股份有限公司

台灣一廠:台南市永康工業區興工路3號 台灣二廠:台南市永康區蔦松三街81巷2號

Factory 1: No.3, Shing Gong Rd., Yong Kang Dist., Tainan City, Taiwan.

Factory 2: No.2, Ln. 81, Niaosong 3rd St., Yong Kang Dist., Tainan City, Taiwan

Tel: +886-6-2438586 Fax: +886-6-2434205

HTTP://WWW.KNEADER.COM.TW E-MAIL: SALES@KNEADER.COM.TW