



Twin Head High Speed Blown Film Machine

YHF-2



YI HUI MACHINERY INDUSTRY CORPORATION

No.256-1, Lane 619, Minghsing Rd., Tainan, Taiwan 702 Website : www.yihui.com.tw
Tel: +886-6-2961492 Fax: +886-6-2626193 E-mail: sales@yihui.com.tw



雙模頭吹袋機 / 吹膜機

Two Head Blown Film Machine

FEATURE

- High performance main motor with Two Dies and one Screw extrusion.
- Great mixing quality from screw and barrel results in good homogeneity and high output

SPECIFICATION

MODEL	YHF-2-45	YHF-2-50	YHF-2-55	YHF-2-65
RAW MATERIAL	HDPE/LDPE			
SCREW	45mm	50mm	55mm	65mm
SCREW L/D	28:1	28:1	28:1	28:1
SCREW MATERIAL	SKD-61 Hardening and Tempering, Polishing, Nitride and Hard Chrome Plating			
BARREL MATERIAL	SACM-645 Hardening and Tempering, Nitride and Polishing			
FILM WIDTH MAX.	400mm	500mm	600mm	800mm
FILM THICKNESS	HD:0.01-0.06mm LD:0.02-0.1mm	HD:0.01-0.06mm LD:0.02-0.1mm	HD:0.01-0.06mm LD:0.02-0.1mm	HD:0.01-0.06mm LD:0.02-0.1mm
MAX. OUTPUT	40KG/HR	50 KG/HR	60 KG/HR	80 KG/HR
MAIN MOTOR	20 HP	30 HP	40 HP	50 HP
INVERTER	FUJI (MADE IN JAPAN)			

Design and Specification Subject to change without notice.

