

PHOENIX SERIES

Cost-Effective and Productive Solutions

PET Stretch Blow Moulding Machine



**銓寶 鳳凰系列
PET 雙軸延伸拉吹機**

PHOENIX SERIES

PET Stretch Blow Moulding Machine

鳳凰系列 PET 雙軸延伸拉吹機



CPSB-TSS6000



銓寶鳳凰系列 – PET 雙軸延伸拉吹機

銓寶鳳凰系列擁有合理的價格與高穩定性，且佔地面積小，操作簡單、維修容易。泛用型加熱設計，可適用多種產品，包括礦泉水、碳酸飲料、調味料、茶、果汁、蒸餾水、酒精飲料、食用油、清潔液、化妝品等。

為提升 PET 拉吹機的安全性與耐久性，變更感測 SENSOR 檢測方式，提升耐久性與穩定度，並增加關模檢測 SENSOR，確保連桿位置無異常，提升機器安全等級。

適用少量多樣的生產方式，可選配為全電機台。





CHUMPOWER Phoenix Series – PET Stretch Blow Moulding Machine

CHUMPOWER Phoenix Series has reasonable price and high stability with low occupation of ground area, simple operation, and easy maintenance. Its universal heating design is suitable for many kinds of products such as mineral water, soda, seasoning, tea, juice, distilled water, alcohol drink, cooking oil, cleaning solution, and cosmetics... etc.

To increase the safety and durability of PET blow molding machine, the detecting method of detection sensor has been altered. The durability and stability have both been improved. Another detection sensor for mold closing is added to

ensure the toggle position is correct and overall safety level of machine is upgraded. Suitable for manufacturing of few volumes in multiple shapes with an option to become all-electric platform.



FULLY ELECTRIC

Stretch Blow Moulding Machine

鳳凰全電式機台



SERVO-ELECTRIC TECHNOLOGY

High Precision

High Reliability

Energy Saving

FEATURES

- Fast and smooth servo-driven transferring system
- Low vibration and quiet servo-driven clamping system
- Servo-driven stretch rod assembly for convenient adjustment
- Featuring heating output compensation system
- Air recovery system to reuse the waste air

機台特性

- 移位伺服，快速穩定
- 拉吹伺服，調整方便
- 高壓吹氣，回收再利用
- 成型伺服，低震動、低噪音

工程規格表 Specification	模穴數 Number of cavities (cavities)	瓶子最大容量 Max. capacity (ltr)	最大牙部尺寸 Max. neck diameter (mm)	最大瓶身直徑 Max. diameter *1 (mm)	最大瓶身高度 Max. height (mm)	理論產能 Theoretical output *2 (B.P.H.)	機台尺寸 Size (L x W x H) (mm)	機台重量 Weight (kg)
CPSB-TS2000	2	1.5	38	105	320	2000	2400x2150x2500	2700
CPSB-TS2000E	2	1.5	38	105	320	2800	2400x2150x2500	2700
CPSB-TS2000W	2	1.5	63	105	320	2000	2400x2150x2500	2700
CPSB-TS2000WE	2	1.5	63	105	320	2800	2400x2150x2500	2700
CPSB-TS2000H	2	1.5	38	105	320	900	2400x2150x2500	2700
CPSB-T3000	3	3	38	140	350	3000	4000x2150x2500	6500
CPSB-T3000E	3	3	38	105	350	4000	4000x2150x2500	6500
CPSB-TSS3000	3	0.6	38	68	240	3000	2400x2150x2500	2700
CPSB-TSS3000E	3	0.6	38	68	240	4000	2400x2150x2500	2700
CPSB-TS4000	4	1.5	38	105	320	4000	4000x2150x2500	6500
CPSB-TS4000E	4	1.5	38	105	320	5600	4000x2150x2500	6500
CPSB-TS4000W	4	1.5	63	105	320	4000	4000x2150x2500	6500
CPSB-TS4000WE	4	1.5	63	105	320	5000	4000x2150x2500	6500
CPSB-TS4000H	4	1.5	38	105	320	1800	4000x2150x2500	6500
CPSB-TSS6000	6 (3)	0.6	38	68 (105)	240	6000	4000x2150x2500	6500
CPSB-TSS6000E	6 (3)	0.6	38	68 (105)	240 (320)	8000	4000x2150x2500	6500
CPSB-TSS6000H	6	0.6	38	68	240	2700	2400x2150x2500	6500

*1 The actual output depends on the preform quality and bottle shape. 最終產能須依據瓶胚、瓶型而定。

*2 Specification are subject to change without notice. 規格有變更時，恕不另行通知。

Chum Power

鈺寶工業股份有限公司
CHUMPOWER MACHINERY CORP.

414 台中市烏日區中山路三段 688-1 號
No.688-1, Sec. 3, Zhongshan Rd., Wuri Dist, Taichung City 414, Taiwan
TEL: 886-4-2338-8289 FAX: 886-4-2338-0219
Email: servers@chumpower.com
web: pet.chumpower.com

