

Servo Motor Driven Double Layer Bag Making Machine

伺服馬達驅動 雙層式製袋機

SHTF



興享機器興業有限公司
SING SIANG MACHINERY CO., LTD.

70969台灣台南市和順工業區永安路66號 TEL : +886-6-356-3297 FAX : +886-6-356-7267
66 Yung-An Road, Ho-Sun Industrial, Tainan, Taiwan

<http://www.bag-machine.tw>

Email: ssmtaiwan@gmail.com

Toll-Free Service Hot line: 0800-030-567

Web Site: www.興享.tw





● 背心袋用熱針輸送帶 Hot Pin Conveyor(For T-Shirt Bag)



● 雙層熱封鋼刀 Double Layer Sealing Blade



● 雙層入料裝置 Double Layer Infeed Device

特色：

1. 單伺服馬達驅動、機體傳動輕快、穩定、每分鐘可產120個袋子。
2. 專為有電腦操作障礙者所設計的人性化電腦操作面板，易懂易操作。
3. 電腦按鍵式製袋長度自動調整，出袋長度精準、廢料少。
4. 機器結構設計精簡、組裝精密，牢固耐用、保養簡易。
5. 操作簡便、封切口整齊美觀又牢固。
6. 電眼印刷追蹤、袋子印刷位置精準，當發現印刷失準機器自動停機。
7. 選購熱針輸送帶，可做背心袋。

Features :

1. Servo motor driven, efficient mechanical structure produce 120 bags per minute.
2. User-friendly control panel, easy to understand easy to operate.
3. Digital control for production length adjusting, precise and less wastage.
4. Simple design, assemble precisely, durable, and easy for replaced maintaining.
5. Easy operating, pleasant cutting and sealing, with high firmness and no scratch.
6. Real time printing tracing control for accurate registration, when printing error occurred machine will stop automatically.
7. Optional accesories: hot pin conveyor stack for T-Shirt bag making machine.

規格 SPECIFICATION :

型號 Model	產能 Output Cycle/min.	封寬 Bag Width	封長 Bag Length	封厚 Film Thickness	主馬達 Main Motor	總電量 Power Consumption	機器尺寸 Machine Dimension (LxWxH)	淨重 Machine Weight	毛重 Gross Weight
SHTF-30A	Max 120	Max 725mm	Max 1820mm	0.01~0.06 mm	2HP4P	3.5KW	5880×1430×2010	1450kg	1900kg
SHTF-36A	Max 100	Max 860mm	Max 1820mm	0.01~0.06 mm	2HP4P	4.0KW	5880×1585×2010	1650kg	2100kg
SHTF-42A	Max 90	Max 1010mm	Max 1820mm	0.01~0.06 mm	2HP4P	4.5KW	5880×1740×2010	1850kg	2300kg
SHTF-50A	Max 60	Max 1210mm	Max 2540mm	0.01~0.06 mm	2HP4P	5.0KW	5880×1940×2010	2050kg	2500kg
SHTF-60A	Max 60	Max 1470mm	Max 2540mm	0.01~0.06 mm	2HP4P	6.0KW	5880×2200×2010	2250kg	2700kg

Specification are subject to change without notice (變更設計恕不另行通知)