

Recycled Plastic Waste Pelletizer Machine Die Face Cutting System

Model AP-100DR



APEX-PLAS®



Die Cut Unit
模頭切設備



Storage Bucket
收集桶



Dehydrator
脫水機

Model/Specification 型號/規格	AP-85DR	AP-100DR	AP-125DR	AP-150DR
MAIN EXTRUDER 押出主機				
EXTRUSION CAPACITY 押出量	100~180 Kg/Hr	180~250 Kg/Hr	250~390 Kg/Hr	380~500 Kg/Hr
Screw diameter 螺桿直徑	Ø85 mm	Ø100 mm	Ø125 mm	Ø150 mm
Screw length-to-diameter ratio 螺桿長徑比	32/1	32/1	32/1	32/1
Drive horsepower 傳動馬力	50HP	75HP	100HP	150HP
Automatic temperature control 自動溫度控制器	5 Zones	7 Zones	9 Zones	11 Zones
Heat capacity 電熱容量	28KW	32KW	52KW	74KW
Force feeding motor 強制給料馬達	3HP	5HP	7½HP	7½HP
Hydraulic screen changer motor 油壓換網馬達	3HP	5HP	7½HP	7½HP
Water circulation equipment 水循環設備				
Water circulation pump 水循環泵浦	2HP	2HP	3HP	5HP
Vibration screening machine 震動篩選機				
Drive horsepower 傳動馬力	1/5HP × 2Pcs	1/4HP × 2Pcs	1/4HP × 2Pcs	1/2HP × 2Pcs
Processing capacity 處理能力	150Kgs/Hr	200Kgs/Hr	350Kgs/Hr	500Kgs/Hr
Blowerhorsepower 送風機馬力	2HP	3HP	5HP	7½HP
Storage tank 儲料桶				
Storage capacity 儲存容量	600Kg	800Kg	1000Kg	1500Kg



APEX-PLAS® INDUSTRIAL CO., LTD.

11F-1, No.393, Fuxing Rd., Taoyuan City, Taoyuan County 33066, Taiwan
Tel : +886-3-3319116 Fax : +886-3-3319339

www.apexplas.com
E-mail : ap@apexplas.com