



www.fcs.com.tw

SHOW GUIDE

- >> *Fast response*
- >> *Customer oriented*
- >> *Service differentiation*

**Orange County Convention Center
Orlando, Florida USA**

Booth No.W303




**NPE2015: THE INTERNATIONAL
PLASTICS SHOWCASE**

March 23-27, 2015 | Orlando, Florida USA

www.npe.org

BOOTH LAYOUT



DATE : 3/23~3/27

Booth No.W303



**NPE2015: THE INTERNATIONAL
PLASTICS SHOWCASE**

In Mold Labeling Turnkey Solution



High Speed / Closed Loop Hybrid Injection Molding Machine

- Adopting (ESD) electric screw drive structure, it offers the accuracy and energy-saving features.
- Applied Germany MOOG closed-loop high-respond servo valve and accumulator.
- With hybrid-structure, it could ideally save 70%~80% energy.

Specification

Machine Model	AF-200
Clamping Force	200 ton
Screw Diameter	1.73 inch (44 mm)
Injection Speed	19.68 inch/sec (500 mm/sec)
Distance Between Tie Bars	20 x 20 inch (510 x 510 mm)

Product

Part	Yogurt box
Volume	200 cc
Thickness	0.017 inch (0.45 mm)
Cavities	2
Material	PP
Cycle Time	4.5 sec

Label Inserting System & Label

Capability	1800 pcs/hr/cav	Label thickness	60μ
Label Q'ty supply	2+2 pcs/time	Label design	Wrap-around oval with bottom label
Total Label Q'ty	2600 pcs/cassette		

Project Partners

 MO CHYI	Mold supplier	 Bourque	Plastic Material
 WIETEC	Robot System	 SHINI	Material Feeding
 DVI	Label	 YUTING	Chiller

Precise Energy-saving Multi-component Molding system



Servo Power-Saving Two Component Injection Molding Machine

- Rotary table controlled by servo valve could shorten rotary time by more than 50%, with more stable rotary speed switch and more precise positioning.
- Adopting high efficiency double servo power system which is certified the first grade of power saving standard ($\leq 0.40\text{kw h/kg}$).
- With accurate confirmation of the rotating position, it protect the mold itself.

Specification

Machine Model	FB-160RV
Clamping Force	160 ton
Screw Diameter	1.18 inch x 2 (30 mm x 2)
Distance Between Tie Bars	28.7 x 15.7 inch (730 x 400 mm)
Rotary Table Diameter	31.89 inch (810 mm)


Product

Part	Brush
Size	3.8 x 1.96 x 1.46 inch (95.5 x 50 x 37 mm)
Weight	47g / pcs
Cavities	1+1
Material	PP+PP
Cycle Time	35 sec

Project Partners

	Mold supplier		Material Feeding
	Robot System		Chiller
	Conveyer Belt		Master Batch
	Plastic Material		

Two-platen Hydra-Mech Molding System



Two Platen Injection Molding Machine

- Two-platen structure has shorter clamping unit which saves the factory space more than 30%, and mold-adjusting only takes 5~10 seconds.
- Rexroth solenoid valve control provides high accuracy of clamping force, the error achieves under $\pm 1\%$.
- Clamping unit without toggle structure which reduces lubrication and maintenance cost.

Specification

Machine Model	LM-900SV
Clamping Force	900 ton
Screw Diameter	3.93 inch (100 mm)
Daylight	74.8 inch (1900 mm)
Distance Between Tie Bars	44.1 x 39.77 inch (1120 x 1010 mm)

Product

Part	Stool
Size	13.46 x 13.46 x 17.36 inch (342 x 342 x 441 mm)
Weight	620 g
Material	PP
Cycle Time	35 sec

Project Partners

	Mold supplier		Material Feeding
	Robot System		Chiller
	Conveyer Belt		Master Batch
	Plastic Material		



MARUKA
www.marukausa.com

FCS
www.fcs.com.tw

FCS Group

Fu Chun Shin Machinery Manufacture Co., Ltd.

No. 269, Baodong Road, Pitou Village, Guanmiao District,
Tainan City 71841, Taiwan.

TEL: +886-6-5950688 • E-mail: fcsco@fcs.com.tw

FAX: +886-6-5951129

Sold and Serviced in America by MARUKA U.S.A. INC.

Maruka U.S.A. Corporate Office-New Jersey

45 Route 46 East, Suite 610 P.O. Box 747 Pine Brook, NJ 07058

TEL : (973)487-3800, (800)631-0426

FAX : (973)244-2147

Maruka U.S.A. - Missouri

1210 NE Douglas Lee's Summit, MO 64086-4604

TEL : (816)524-1811 FAX : (816)524-5444

Maruka U.S.A. - Los Angeles

16440 Manning Way, Cerritos, CA 90703

TEL : (562)926-3654 FAX : (562)926-0884

Maruka U.S.A. - Chicago

1062 Garfield Street Lombard, IL 60148

TEL : (630)953-1707 FAX : (630)953-1753

